

ATP 13



EQUIPMENT

HITCH

- Drawbar adjustable in height
- Hydraulic crutch with hand pump

UNDERCARRIAGE

- Heavy-duty boggie axles
- Heavy-duty parabolic suspension leaves
- Hydraulic braking
- 25 km/h homologation

DUMPING

- Dumping by telescopic cylinder on tractor valves
- Cylinder mounted on support frame and ball-joint connection

DOOR

- 1-part door with hydraulic opening

BODY

- Extra low body integrated into chassis, resting on silent blocks

- Half-round all-HARDOX®450 body
- HARDOX® 450 steel bottom, thickness 5mm
- HARDOX® 450 steel sides, thickness 4mm
- Rocks breaker upper sides
- Lateral sliding ladder
- Double LED lighting with protection grid
- Set of electrical wires protected into chassis

DUMPING

- Dumping by telescopic cylinder on tractor hydraulic valves

OPTIONS

HITCH

- Hydraulic suspension drawbar adjustable in height
- Ø50mm ring on Scharmüller universal plate
- Ø80mm ball on Scharmüller universal plate

UNDERCARRIAGE

- Poclain hydraulic assistance on axles
- Free steering axle
- Mixed hydraulic and air braking
- Other sets of tyres

DOOR

- 2-part door with hydraulic opening

BODY

- On-demand RAL color¹
- Removable headboard for hitch protection
- One-piece mudguards

DUMPING

- Load transfer cylinder on rear axle (for boggie axles)

¹Special painting applied in factory

TECHNICAL DATA												
type	payload kg	volume m ³	in-use dimensions						axles			tyres
			L mm	A mm	B mm	M mm	N mm	H mm	quantity	assembly	brakes mmxmm	
ATP 13	13000	9	4700	2300	800	6250	2550	1400	2	boggie	355x80	385/65R22,5
ATP 16	16000	9	4700	2300	800	6250	2550	1400	2	boggie	400x80	445/65R22,5
ATP 20	20000	15	5450	2350	1080	7300	2550	1520	2	tandem	406x140	445/65R22,5

