

ATP 16



EQUIPMENT

25 km/h homologation

HITCH

- **Hydraulic crutch** with hand pump

UNDERCARRIAGE

- **Heavy-duty** undercarriage
- **Heavy-duty suspensions**
- **Hydraulic** braking

DUMPING

- **Dumping by telescopic cylinder** on tractor valves
- **Cylinder mounted on support frame and ball-joint connection**

DOOR

- **Hydraulic-opening-1-panel door**

BODY

- **Low COG** thanks to overlapped body. Resting on **rubber blocks**

- Full **HARDOX® 450** semi-conical body
- **HARDOX® 450 steel bottom** - thickness 5mm
- **HARDOX® 450 steel sides** - thickness 4mm
- **Rocks-breaker profile** on side tops
- **Double LED lighting** with protection grid
- Electric beam **protected in steel tube**
- **Lateral sliding ladder** with inside footboard

OPTIONS

HITCH

- **Sprung drawbar** adjustable in height
- **Hydraulic drawbar** adjustable in height
- **Ø50 mm hitch** on universal plate

UNDERCARRIAGE

- **Powered axles** with **Poclair hydraulic motors**
- **Passive** steering axle
- **Active** steering axle
- Other **set of tyres**: consult us
- Combined **hydraulic and pneumatic** braking

DOOR

- **Hydraulic-opening-2-panel-door**

BODY

- **On-demand color**¹
- Removable **protection front cap**
- One-piece **mudguard**

¹ special painting applied in factory