

BT 18/25



EQUIPMENT

HITCH

- Sprung drawbar **adjustable in height**
- **Ø50 mm hitch** on universal plate
- **Hydraulic crutch** with hand pump

UNDERCARRIAGE

- **Heavy-duty boggie axles** with high amplitude
- **Heavy-duty suspensions**
- **Hydraulic braking** with heavy-duty brakes

DUMPING

- **PTO-driven hydraulic circuit** with piston pump
- **DUMPER-type wide angle dumping**
- **Fast dump cycle** by high speed distributor
- **Double-acting cylinders** with ball-joint connections

DOOR

- **Raised rear edge for use without door**

BODY

- **HARDOX® 450 steel bottom** - thickness 10 mm

- **Domex® 450 steel sides** - thickness 10 mm
- **High strength steel chassis**
- **Rocks-breaker profile** on side tops
- **Double LED lighting** with protection grid
- Electric beam **protected in steel tube**

OPTIONS

40 km/h homologation

HITCH

- **Hydraulic drawbar** adjustable in height
- **Ø80 mm Scharmüller ball** on universal plate

UNDERCARRIAGE

- **Poclain hydraulic powered axles**
- Other **set of tyres**: consult us

DOOR

- **Automatic door with high amplitude**

BODY

- **On-demand color**¹
- **Full HARDOX®** body
- **Anti-tilting cylinders** on rear axles

¹ special painting applied in factory