

CP 35



EQUIPMENT

CE marking

HITCH

- Classic drawbar¹
- BNA hitch

UNDERCARRIAGE

- Suspension of axles **by compression**
- **Inertia braking** of each axles

BODY

- **Automatic crutches** at lowering of ramps
- **Electric beam² protected in steel tube**
- **One-piece durable steel** mudguard
- 4 CE stowage rings
- Steel + wood ramps, **adjustable in track**
- **One-piece welded** frame
- Non-slip metal floor (diamond plate) or wood floor
- Crutch with resting sole

OPTIONS

HITCH

- **Gourdon® hydraulic drawbar**¹
- Ø50 mm ball-joint towing connection³
- DIN 40 hitch for Rockinger hook³

UNDERCARRIAGE

- Spare wheel
- **Heavy-duty Jockey wheel**

BODY

- **Safety chocks** for composite floor
- **Aluminium** ramps
- **LED lighting**
- **Waterproof** documents support
- **On-demand RAL color**⁴
- Kit of 2 lashings with hooks
- Adjustable stop

1 manual adjustement of coupling height

2 7/13 pins with adaptator

3 delivered in addition to BNA hitch

4 special painting applied in factory

TECHNICAL DATA												
TYPE	GLW ¹	PL ²	in-use dimensions				overall dimensions ³		ramps			tyres
	kg	kg	L mm	A mm	H mm	B mm	M mm	N mm	length mm	width mm	track mm	
CP 35	3500	2800	3400	1650	520	260	4960	2250	1500	280	350	195x14
CP 35 PB	3500	2800	3600	1700	530	260	5033	2270	1500	280	400	195x14
CP 35 SN	3500	2800	3400	1650	450	260	4880	2250	1500	280	350	195x14

¹ Gross laden weight ² Payload ³ with Gourdon® hydraulic drawbar adjustable in height

