

G 100



EQUIPMENT

HITCH

- Sprung drawbar **adjustable in height** on three positions
- **Hydraulic crutch** with hand pump

UNDERCARRIAGE

- **Heavy-duty** axle
- **Hydraulic** braking
- Parking brake

DUMPING

- **Hydraulic dumping** on tractor valves

DOOR

- **Automatic-opening-1-panel-door** with pendulum movement

BODY

- **Conical body** with front sloping panel
- **SSAB Domex® 500 steel sides** - thickness 4 mm
- **SSAB Domex® 500 steel bottom** - thickness 5 mm
- **High strength steel chassis** - thickness 5 mm

- **Sliding access ladder** on front panel
- **Low COG** thanks to overlapped body. Resting on **rubber blocks**
- **LED lighting** with protection grid

OPTIONS

DUMPING

- **PTO-driven dumping** with independant hydraulic circuit

DOOR

- **Grain hatch** with lever
- **Automatic-opening-2-panel-door**
- **Hydraulic-opening-1-panel-door**
- **Hydraulic-opening-2-panel-door**
- **Spillway** on hatch

BODY

- **Non-toxic paint** ¹
- **Visual level** on front panel
- Steel sides - height **350 mm**
- Steel sides - height **500 mm**
- Aluminium sides - height **350 mm**
- Aluminium sides - height **500 mm**
- **Beacon bracket**

SHEETINGS

- **Sheeting hoop and hooks**
- **Simple sheeting with bungee cords**

¹ special painting applied in factory

CHASSIS

Chassis is made of high-strength-steel box girders. The monoblock cylinders bracket optimizes strength and weight.

Thanks to the reduced width of the chassis COG height of the trailer is lowered.

AUTOMATIC REAR DOOR

Thanks to its pendular kinematic, the rear door opening is fastened and products like silage or manure easily dumped.