

GVM 180



EQUIPMENT

HITCH

- Sprung drawbar adjustable in height sur 3 positions
- Ø50 mm hitch on Scharmüller universal plate
- Hydraulic crutch with hand pump

UNDERCARRIAGE

- Heavy-duty tandem axles
- Hydraulic braking and nitrogen emergency brake

DUMPING

- PTO-driven dumping with independant hydraulic circuit

DOOR

- 1-part door with hydraulic opening
- Grain hatch with lever

BODY

- Conical body with front sloping panel and visual level
- SSAB Domex® 500 steel sides, thickness 4 mm
- SSAB Domex® 500 steel bottom, thickness 5 mm
- SSAB Domex® 500 tubular steel chassis, thickness 6 mm
- Sliding access ladder on front panel

- Mudguards integrated into the body
- Toolbox
- Low-height body integrated into chassis with resting on rubber blocks
- LED lighting with protection grid
- Bracket and power supply for rear beacon
- Rear bumper, orange lights and marker lights, Standard 2020

OPTIONS

HITCH

- Hydraulic suspension drawbar
- Ø80 mm ball on Scharmülleruniversal plate
- Double front crutch on tractor valves

UNDERCARRIAGE

- Free steering rear axleActive steering for one axle¹
- Self steering for two axles¹
- Steering axle locking indicator
- Air suspensions (40km/h homologation)
- Mixed hydraulic and air braking (25km/h homologation)
- Air braking (40km/h homologation)
- Air braking predisposition for 40km/h homologation

DUMPING

- Mixeddumping on PTO or tractor valves
- Hydraulic dumping on tractor valves (PTO-less)
- Hydraulically assisted descent

DOOR

- 1-part MAXI VRAC® door with high amplitude (+2m³)
- 2-part door with hydraulic opening
- Spillway on hatch

BODY

- On-demand RAL color²
- Steel sides - height 350mm
- Sillage steel or aluminium extensions - height 500mm on 1.40m monoshell body

COVERS

- Covershoop and hooks
- Simple sheeting with bungee cords
- Rolling sheeting operated from ground floor

¹ Option "Self steering rear axle" must be included

² Special painting applied in factory

