

GVM 240 XL



EQUIPMENT

HITCH

- Sprung drawbarsur **3 positions**
- **Ø50 mm hitch**on universal plate
- **Hydraulic crutch**with hand pump

UNDERCARRIAGE

- Heavy-duty**axles**
- **Hydraulic braking**and nitrogen emergency brake
- Rear**passive steering axle**

DUMPING

- **Dumping by front telescopic cylinder**with turbocompressor without PTO

DOOR

- Hydraulic-opening-1-panel door
- Grain hatch with lever

BODY

- Conical body with front sloping panel and visual level
- **SSAB Domex® 500 steel sides**- thickness 4 mm

- **SSAB Domex® 500 steel bottom**- thickness 5 mm
- **SSAB Domex® 500 tubular steel chassis**- thickness 6 mm
- Sliding access ladder on front panel
- Mudguards integrated into the body
- Toolbox
- **Steel extensions**- height 500 mm
- **Low COG** thanks to overlapped body. Resting on rubber blocks
- **LED lighting** with protection grid
- Marker lights, bracket and power supply for rear beacon
- R.I.G. - Rear Impact Guard

OPTIONS

HITCH

- Hydraulic suspensions drawbar
- **Ø80 mm Scharmüller ballon** universal plate
- **Double front crutchon** tractor valves

UNDERCARRIAGE

- **Front passive steering axle**
- **Active steering** for one axle¹
- **Active steering** for two axles¹
- Steering axle **lock indicator**
- **Air suspensions** (40km/h homologation)
- Combined **braking** (25km/h homologation)
- **Air braking** (40km/h homologation)
- **Air braking predisposition** for 40km/h homologation

DOOR

- **Hydraulic-opening-MAXI BULK® door** with high amplitude (+2m³)
- Hydraulic-opening-2-panel door
- Spillway on hatch

DUMPING

- **Hydraulically assisted lowering**

DOOR

- **Hydraulic-opening-MAXI BULK® door** with high amplitude (+2m³)
- Hydraulic-opening-2-panel door
- Spillway on hatch

BODY

- **On-demand RAL color**²

SHEETINGS

- Sheeting hoop and hooks
- Simple sheeting with bungee cords
- Rolling sheeting operated from ground floor

¹ needs the option "passive steering axle" included

² special painting applied in factory

