

PE 6000



EQUIPMENT

CE marking

HITCH

- BNA hitch **adjustable in height**
- Front crutch with resting sole

UNDERCARRIAGE

- **Heavy-duty tandem** axles
- Suspensions by **parabolic leaf springs**
- Air braking **with ABS**

BODY

- **Treated solid wood** floor
- **4 CE stowage rings**
- **Steel + wood ramps adjustable in track**
- Rear ramps **assisted by springs**
- Rear **stabilization** crutches
- **LED lighting**
- **Required lighting 24V**
- Electric beam **protected in steel tube**
- One-piece welded frame
- One-piece durable steel mudguard

OPTIONS

HITCH

- Downlink beam for 15-pin electric plug
- DIN 50x115 hitch
- DIN 40x100 hitch

UNDERCARRIAGE

- Spare wheel

BODY

- **Waterproof** documents support
- **On-demand color**¹
- **Aluminium** ramps
- Kit of 2 lashings with hooks

¹ special painting applied in factory

TECHNICAL DATA															
TYPE	GLW ¹	PL ²	in-use dimensions				overall dimensions		coupling height		ramps				simple tyres
	kg	kg	L mm	A mm	H mm	B mm	M mm	N mm	mini mm	maxi mm	length mm	width mm	min. track mm	slope G %	
PE 6000	6000	4240	4100	1990	640	300	5860	2550	600	820	2000	300	580	18	215/75R17,5
PE 8000	8000	6100	4100	1990	640	300	5860	2550	600	820	2000	300	580	18	215/75R17,5

¹ Gross laden weight ² Payload

