

PE80RD



EQUIPMENT

CE marking

HITCH

- BNA hitch **adjustable in height**
- Front crutch with resting sole

UNDERCARRIAGE

- **Heavy-duty tandem** axles
- Suspensions by **parabolic leaf springs**
- Air braking **with ABS**

BODY

- **Combined steel¹ and exotic wood** floor
- **8 CE stowage rings**
- **Steel + wood ramps adjustable in track**
- Rear ramps **assisted by springs**
- Rear **stabilization** crutches
- **0,60m cutaway for an eased loading**
- **LED lighting**
- **Required lighting 24V**
- Electric beam **protected in steel tube**
- One-piece welded frame
- One-piece durable steel mudguard

OPTIONS

HITCH

- Downlink beam for 15-pin electric plug
- DIN 50x115 hitch
- DIN 40x100 hitch

UNDERCARRIAGE

- Spare wheel

BODY

- **Waterproof** documents support
- **On-demand color²**
- **Aluminium** ramps
- Kit of 2 lashings with hooks

¹ with non-slip slats

² special painting applied in factory

TECHNICAL DATA															
TYPE	GLW ¹	PL ²	in-use dimensions				overall dimensions		coupling height		ramps				simple tyres
	kg	kg	L mm	A mm	H mm	B mm	M mm	N mm	mini mm	maxi mm	length mm	width mm	min. track mm	slope G %	
PE 80RD	8880	6480	4600	2400	840	-	6670	2400	640	970	2000	300	460	16	215/75R17,5

¹ Gross laden weight ² Payload

