

## PEA 890



### EQUIPMENT

#### HITCH

- Drawbar **adjustable in height** on 3 positions
- Crutch with resting sole and **crank jack**

#### UNDERCARRIAGE

- **Heavy-duty** axles
- **Hydraulic braking** and parking brake

#### TILTING

- Fixed flatbed

#### BODY

- **Low-height floor** with wheels outside of flatbed
- **Treated solid wood** floor
- **4 CE stowage rings**
- **Steel + wood ramps** adjustable in track
- Ramps **assisted by springs**
- **Led lighting, 12 V required lighting**
- Electric beam **protected in steel tube**
- One-piece road-like welded frame
- Supports under flatbed
- One-piece durable steel mudguard

## OPTIONS

- Spare wheel under flatbed mounted on frame with hoise

TECHNICAL DATA															
TYPE	GLW <sup>1</sup> t	PL <sup>2</sup> t	in-use dimensions			overall dimensions		axles			ramps			tyres	
			L mm	A mm	H mm	M mm	N mm	data nb axles x section (mm) / nb <sub>holes</sub>	brakes mm x mm	long. mm	larg. mm	min. track mm	assembly	size	
PEA 890 *	8,9	7,5	4100	1990	640	6040	2550	2x70/8	300x60	2000	300	580	simple	235/75 R17,5	
PEA 80	8	6,5	4600	2400	885	6745	2390	2x80/8	300x60	2000	300	460	simple	235/75 R17,5	
PEA 130	13	10	6000	2500	920	8217	2490	2x80/8	300x90	1300	500	830	simple	235/75 R17,5	
PEA 240	23,5	19	7100	2550	950	9227	2550	2x120/8	300x140	1300	500	900	twin	235/75 R17,5	
PEA 320	32	24	9000	2550	1070	11315	2550	3x120/10	300x140	1300	500	980	twin	235/75 R17,5	

<sup>1</sup> Gross laden weight <sup>2</sup> Payload \* Low mounting with wheels outside of the flatbed

