

## PEB 160



### EQUIPMENT

CE marking

#### HITCH

- BNA hitch **adjustable in height**

#### UNDERCARRIAGE

- **Heavy-duty tandem** axles
- Suspensions by **parabolic leaf springs**
- Air braking **with ABS**
- 4 twin wheels
- Mechanical **parking brake**

#### TILTING

- Tilting flatbed **by gravity** with damping cylinders
- **Flatbed lock system** in road mode

#### BODY

- **Combined steel<sup>1</sup> and exotic wood** floor
- 8 **CE stowage rings**
- **Steel + wood ramps adjustable in track**
- Rear ramps **assisted by springs**
- **LED lighting**

- Required lighting 24V
- Electric beam **protected in steel tube**
- **One-piece welded frame**

## OPTIONS

### HITCH

- Downlink beam for 15-pin electric plug
- DIN 50x115 hitch

### UNDERCARRIAGE

- Spare wheel

### BODY

- **Waterproof** documents support
- Toolbox
- **On-demand color2**

1 with **non-slip** slats

2 special painting applied in factory

TECHNICAL DATA															
TYPE	GLW <sup>1</sup> kg	PL <sup>2</sup> kg	dimensions				coupling		length mm	width mm	ramps		axles	tyres	
			L mm	M mm	H mm	A mm	min. height mm	max. height mm			min. track mm	slope G %		assembly	size
PEB 111	11400	8580	6100	8130	910	2500	677	877	1400	500	860	14	2	simple	215/75R17,5
PEB 160	16000	12000	7100	9370	950	2550	810	980	1400	500	930	16	2	twin	215/75R17,5
PEB 190	19000	15000	7100	9370	950	2550	810	980	1400	500	930	16	2	twin	215/75R17,5
PEB 240	24000	17000	7500	9650	950	2550	870	1050	1400	680	950	15	3	twin	235/75R17,5
PEB 260	26000	19000	7500	9650	950	2550	870	1050	1400	680	950	15	3	twin	235/75R17,5
PEB 310	31000	24500	7500	9650	950	2550	870	1050	1400	680	950	15	3	twin	235/75R17,5

<sup>1</sup> Gross laden weight    <sup>2</sup> Payload

