

PEB 260



EQUIPMENT

CE marking

HITCH

- BNA hitch **adjustable in height**
- **Hydraulic crutch** with hand pump

UNDERCARRIAGE

- **Heavy-duty tridem** axles
- Suspensions by **parabolic leaf springs**
- Air braking **with ABS**
- 12 twin wheels
- Mechanical **parking brake**

TILTING

- Tilting flatbed **by 24V electro-pump**
- **Flatbed lock system** in road mode
- Predisposition for expander inside the flatbed

BODY

- **Combined steel and exotic wood** floor
- 10 **CE stowage rings**
- **Steel + wood ramps** adjustable in track

- Rear ramps **assisted by springs**
- **Hydraulic lifting** of ramps
- **LED lighting**
- **Required lighting 24V**
- Electric beam **protected in steel tube**
- **One-piece welded frame**
- Lateral guides for tracks

OPTIONS

HITCH

- Downlink beam for 15-pin electric plug
- DIN 50x115 hitch

UNDERCARRIAGE

- **Spare wheel**

BODY

- **Hydraulic adjustment** of ramps track
- **Waterproof** documents support
- Toolbox
- **On-demand color²**
- Expanders
- Bucket resting support

1 with **non-slip** slats

2 special painting applied in factory

TECHNICAL DATA															
TYPE	GLW ¹	PL ²	dimensions				coupling		ramps				axles	tyres	
	kg	kg	L mm	M mm	H mm	A mm	min. height mm	max. height mm	length mm	width mm	min. track mm	slope G %		assembly	size
PEB 111	11400	8580	6100	8130	910	2500	677	877	1400	500	860	14	2	simple	215/75R17,5
PEB 160	16000	12000	7100	9370	950	2550	810	980	1400	500	930	16	2	twin	215/75R17,5
PEB 190	19000	15000	7100	9370	950	2550	810	980	1400	500	930	16	2	twin	215/75R17,5
PEB 240	24000	17000	7500	9650	950	2550	870	1050	1400	680	950	15	3	twin	235/75R17,5
PEB 260	26000	19000	7500	9650	950	2550	870	1050	1400	680	950	15	3	twin	235/75R17,5
PEB 310	31000	24500	7500	9650	950	2550	870	1050	1400	680	950	15	3	twin	235/75R17,5

¹ Gross laden weight ² Payload

