

## RB 35



### EQUIPMENT

CE marking

#### HITCH

- **?V-like? shape** durable drawbar
- Classic drawbar fixed coupling height
- **Hook hitch** for ball-joint towing connection

#### UNDERCARRIAGE

- **Heavy-duty** axles and tyres
- Suspensions of axles **by torsion**
- **Inertia braking** of each axle
- Heavy-duty **Jockey wheel**

#### TILTING

- **Rear dumping** by hydraulic cylinder and hand crutch
- **One-piece welded** durable flatbed

#### BODY

- Lighting with protection grid
- Electric beam<sup>1</sup> **protected in steel tube**
- **One-piece welded and galvanized** frame
- Chassis stringers made of **durable steel tubes**
- **Folding and removable** sides

### OPTIONS

## HITCH

- BNA hitch instead of hook hitch
- **Gourdon® hydraulic drawbar<sup>2</sup>**

## UNDERCARRIAGE

- Spare wheel

## TILTING

- **3-way dumping (lateral dumping in addition to rear dumping)**
- **Electro-pump** with plug on tractor output
- **Electro-pump** with independant battery

## BODY

- LED lighting
- Ladder support
- **Non-slip steel ramps** with rear stabilization crutches
- **Aluminium ramps** with rear stabilization crutches
- **Fenced** front pannel – height 1.00m
- **Fenced** sides – height 1.00m
- **On-demand color<sup>3</sup>**

<sup>1</sup> 7/13 pins with adaptor

<sup>2</sup> hydraulic adjustment of coupling height

<sup>3</sup> special painting applied in factory

## TECHNICAL DATA

TYPE	GLW <sup>1</sup>	PL <sup>2</sup>	in-use dimensions				overall dimensions		coupling			rampes			tyres
			L	A	H	B	M	N	min. height	max. height	fixed height	length	width	min. track	
	kg	kg	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	
<b>RB 25</b>	2500	1690	3000	1700	740	380	4500	1800	300	980	430	2000	300	-	185x14
<b>RB 35</b>	3500	2570	3000	1700	750	380	4500	1800	300	980	430	2000	300	-	195x14

<sup>1</sup> Gross laden weight <sup>2</sup> Payload <sup>3</sup> with Gourdon® hydraulic drawbar adjustable in height

