

## RCM 24



### EQUIPMENT

#### HITCH

- Sprung drawbar on three positions
- Hydraulic crutch with hand pump

#### UNDERCARRIAGE

- Heavy-duty low-height chassis
- Rear (anti-tilting)
- Hydraulic braking
- Nitrogen emergency brake

#### HOOK

- Palfinger® POWER hooklift bolted on chassis
- Rear hydraulic locking of the container

#### CHASSIS

- Low-height tubular chassis
- HSLA steel, thickness 8mm

### OPTIONS

#### HITCH

- Ø80 mm ball on Scharmüller universal plate
- Ø50 mm ring on Scharmüller universal plate

#### **UNDERCARRIAGE**

- Free steering rear axle
- Self for one axle
- Air suspension on tandem (40km/h homologation)
- Airbraking (40km/h homologation)
- Steering axle locking indicator
- Mixed braking (25km/h homologation)

#### **HOOK**

- Double hydraulic line with 2 rear push-pull
- Additional articulation on hooklift
- Rear lifting
- Front hydraulic locking of the container
- Remote control

#### **CHASSIS / CONTAINERS**

- Fixed mudguards
- Steering mudguards
- Agriculture container on support frame (28m<sup>3</sup> volume), various options of mechanical or hydraulic opening
- Construction container on support frame (12m<sup>3</sup> volume), various options of mechanical or hydraulic opening
- Machinery flatbed, from 14 to 20T of payload
- Watering tank, from 6 000 to 22 000L of volume
- Pumping tank, from 6 000 to 22 000L of volume