

RCM 32



EQUIPMENT

HITCH

- Sprung drawbar on three positions
- Hydraulic crutch with hand pump

UNDERCARRIAGE

- Heavy-duty tridem axles with connecting rods on low-height chassis
- Free steering rear axle
- Rear (anti-tilting)
- Hydraulic braking
- Nitrogen emergency brake

HOOK

- Palfinger® POWER hooklift bolted on chassis
- Rear hydraulic locking of the container

CHASSIS

- Reduced height tubular chassis
- HSLA steel, thickness 10mm

OPTIONS

HITCH

- Ø80 mm ball on Scharmülleruniversal plate
- Ø50 mm ring on Scharmülleruniversal plate

UNDERCARRIAGE

- Free steering front axle
- Self for two axles
- Air suspension on tridem (40km/h homologation)
- Airbraking (40km/h homologation)
- Steering axle locking indicator
- Mixed braking (25km/h homologation)

HOOK

- Double hydraulic line with 2 rear push-pull
- Additional articulation on hooklift
- Rear lifting
- Front hydraulic locking of the container
- Remote control

CHASSIS / CONTAINERS

- Fixed mudguards
- Steering mudguards
- Agriculture container on support frame (28m³ volume), various options of mechanical or hydraulic opening
- Construction container on support frame (12m³ volume), various options of mechanical or hydraulic opening
- Machinery flatbed, from 14 to 20T of payload
- Watering tank, from 6 000 to 22 000L of volume
- Pumping tank, from 6 000 to 22 000L of volume