

## RMG 8



### EQUIPMENT

#### HITCH

- Sprung drawbar **adjustable in height** on 3 positions
- Crutch with resting sole and **crank jack**

#### UNDERCARRIAGE

- **Heavy-duty** axles
- **Hydraulic braking**
- Parking brake

#### DUMPING

- **Hydraulic dumping** on tractor valves

#### DOOR

- **Mechanical-opening-2-panel-door**
- Grain hatch with lever

#### BODY

- Sides and extensions **in two parts**
- **SSAB Domex® 500 steel sides** - thickness 4mm
- **SSAB Domex® 500 steel bottom** - thickness 5mm
- **High strength steel chassis** - thickness 3mm

- Rectangular chassis

## OPTIONS

### HITCH

- Turning ring
- **Hydraulic crutch** with hand pump

### DUMPING

- **3-way dumping** with rear and lateral dumping

### DOOR

- Spillway on hatch

### BODY

- **On-demand RAL color**<sup>1</sup>
- Empty floor<sup>2</sup>
- **Fenced extensions - height 1m**
- Beacon bracket

<sup>1</sup> special painting applied in factory

<sup>2</sup> without sides and extensions

TECHNICAL DATA												
TYPE	PL <sup>1</sup>	in-use dimensions				min. volume w/o extensions m <sup>3</sup>	extensions mm	overall dimensions		axles		standard tyres <sup>2</sup>
		L mm	A mm	B mm	H mm			M mm	N mm	data nb axle x section (mm) / nb holes	brakes mm x mm	
RMG 3	3	3000	1700	500	907	3	–	4120	1810	1x60/6	250x60	10x15
RE 47	4,8	3500	1900	500	950	5,3	300	4730	2010	1x60/6	250x60	11,5x15
RMG 5	4,7	3600	1900	500	991	5,8	350	4950	2010	1x60/6	250x60	11,5x16
RMG 6	6	4000	2000	500	1058	8	500	5360	2110	1x70/6	300x60	13,5x75
RMG 8	8,5	4000	2200	750	1261	11	500	5690	2310	1x80/8	320x75	15x22,5R

<sup>1</sup> Payload <sup>2</sup> other sets of tyres available as options

