

RMG 85



EQUIPMENT

HITCH

- Sprung drawbar **adjustable in height** on three positions
- Crutch with **resting sole and crank jack**

UNDERCARRIAGE

- **Heavy-duty** axle
- **Hydraulic** braking
- **Parking brake**

DUMPING

- **Hydraulic dumping** on tractor valves

DOOR

- Grain hatch with lever
- **Automatic-opening-1-panel-door** with pendulum movement

BODY

- **Conical body** with front sloping panel
- **SSAB Domex® 500 steel sides** - thickness 4 mm
- **SSAB Domex® 500 steel bottom** - thickness 5 mm

- **High strength steel chassis** - thickness 5 mm
- Steel sides - height **350 mm**
- **Sliding access ladder** on front panel
- **Low COG thanks to overlapped body. Resting on rubber blocks**

OPTIONS

HITCH

- Turning ring
- **Hydraulic crutch** with hand pump

DOOR

- **Automatic-opening-2-panel** door
- **Hydraulic-opening-1-panel** door
- **Hydraulic-opening-2-panel** door
- **1-panel-door** with integrated seal for transport of liquids
- Spillway on hatch

BODY

- **Non-toxic paint 1**

SHEETINGS

- Sheeting hoop and hooks
- Simple sheeting with bungee cords

1 special painting applied in factory

AUTOMATIC REAR DOOR

Thanks to its pendular kinematic, the rear door opening is fastened and products like silage or manure easily dumped.