# RPF 350




## EQUIPMENT

CE marking

**HITCH**

- ?**V-like**? **shape** durable drawbar
- Classic drawbar fixed coupling height
- **Hook hitch** for ball-joint towing connection

**UNDERCARRIAGE**

- **Heavy-duty** axles and tyres
- Suspensions of axles **by torsion**
- **Inertia braking** of each axle
- Heavy-duty **Jockey wheel**

**TILTING**

- **One-piece durable steel** flatbed

**BODY**

- Electric beam[1] **protected in steel tube**
- **One-piece durable steel** chassis
- Chassis stringers made of **durable steel tubes**
- **Folding and removable** sides

## OPTIONS

**HITCH**

- BNA hitch instead of hook hitch
- **Gourdon® hydraulic drawbar**[2]

**UNDERCARRIAGE**

- Spare wheel

**TILTING**

- **Rear dumping by hydraulic cylinder and hand crutch**

**BODY**

- LED lighting
- Manual hoist
- Electric hoist
- **Non-slip steel ramps** with rear stabilization crutches
- **Aluminium ramps** with rear stabilization crutches
- **Fenced** front pannel – height 1.00m
- **Fenced** sides – height 1.00m
- **On-demand color**[3]

[1] 7/13 pins with adaptor
[2] hydraulic adjustment of coupling height
[3] special painting applied in factory

**TECHNICAL DATA**

| TYPE | GLW [1] | PL [2] | in-use dimensions | | | | overall dimensions[3] | | coupling | | | ramps | | | tyres |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | kg | kg | L mm | A mm | H mm | B mm | M mm | N mm | min. height mm | max. height mm | fixed height mm | length mm | width mm | min. track mm | |
| RPF 250 | 2500 | 1920 | 4000 | 2000 | 650 | 380 | 5300 | 2080 | 300 | 980 | 430 | 2000 | 300 | 300 | 155/70/12 |
| RPF 350_L1 | 3500 | 2570 | 4000 | 2000 | 700 | 380 | 5300 | 2080 | 300 | 980 | 430 | 2000 | 300 | 300 | 195X14 |
| RPF 350_L2 | 3500 | 2500 | 4500 | 2000 | 700 | 380 | 5800 | 2080 | 300 | 980 | 430 | 2000 | 300 | 300 | 195X14 |
| RPF 350_l2 | 3500 | 2440 | 4500 | 2200 | 700 | 380 | 5800 | 2280 | 300 | 980 | 430 | 2000 | 300 | 300 | 195X14 |
| RPF 350_L3 | 3500 | 2460 | 5000 | 2000 | 700 | 380 | 6300 | 2080 | 300 | 980 | 430 | 2000 | 300 | 300 | 195X14 |

[1] Gross laden weight [2] Payload [3] with Gourdon® hydraulic drawbar adjustable in height

