

VPR 350



EQUIPMENT

CE marking

HITCH

- Classic drawbar¹
- BNA hitch

UNDERCARRIAGE

- **Heavy-duty** axles and tyres
- Suspension of axles **by torsion**
- **Inertia braking** of axles
- **Heavy-duty Jockey wheel**

BODY

- **One-piece welded frame**
- **Treated solid wood floor**
- **Steel + wood ramps** adjustable in track
- **Automatic crutches** at lowering of ramps
- **Electric beam²protected in steel tube**
- **One-piece durable steel** mudguard
- 4 CE stowage rings
- **Rear ramps assisted by springs**

OPTIONS

HITCH

- Gourdon® hydraulic drawbar¹
- Ø50 mm ball-joint towing connection³
- DIN 40 hitch for Rockinger hook³

UNDERCARRIAGE

- Spare wheel

BODY

- Composite floor
- Safety chocks for composite floor
- Aluminium ramps
- LED lighting
- Waterproof documents support
- On-demand RAL color⁴
- Kit of 2 lashings with hooks

¹ manual adjustement of coupling height

² 7/13 pins with adaptator

³ delivered in addition to BNA hitch

⁴ special painting applied in factory

| TECHNICAL DATA | | | | | | | | | | | | |
|----------------|------------------|-----------------|-------------------|---------|---------|---------|---------------------------------|---------|--------------|-------------|-------------|-----------|
| TYPE | GLW ¹ | PL ² | in-use dimensions | | | | overall dimensions ³ | | ramps | | | tyres |
| | kg | kg | L mm | A mm | H mm | B mm | M mm | N mm | length mm | width mm | track mm | |
| VPR 130 | 1300 | 1000 | 1760 | 1000 | 425 | 200 | 3350 | 1590 | 1800 | 280 | 400 | 185x14 |
| VPR 200 | 2100 | 1500 | 2600 | 1400 | 460 | 300 | 4250 | 1950 | 1800 | 280 | 400 | 185/70R13 |
| VPR 250 | 2500 | 1940 | 3100 | 1500 | 470 | 300 | 4650 | 2050 | 1800 | 280 | 400 | 185x14 |
| VPR 350 | 3500 | 2750 | 3600 | 1700 | 530 | 300 | 5033 | 2250 | 1800 | 280 | 400 | 195X14 |
| VP 35 | 3500 | 2680 | 3600 | 1900 | 530 | 300 | 5033 | 2450 | 1800 | 280 | 400 | 195X14 |

¹ Gross laden weight ² Payload ³ With Gourdon® hydraulic drawbar adjustable in height

